



# 2001 DYNA GLIDE® SPECIFICATIONS<sup>1</sup>: FXDWG DYNA WIDE GLIDE®

## DIMENSIONS

Length	94.5 in. (2398.4 mm)
Seat Height (measure laden w/ 180 lb. rider)	26.8 in. (680.2 mm)
Seat Height TUV (measure unladen; int'l measure)	(705.6 mm)
Ground Clearance	5.4 in. (136.5 mm)
Rake	32.0 degrees
Trail	5.1 in. (129.4 mm)
Wheelbase	66.1 in. (1677.6 mm)
Tires: Dunlop Harley-Davidson Series D401	
Front Type	D402
Front Size	MH90-21 56H
Rear Type	D401
Rear Size	130/90B16 73H
Fuel Capacity (includes 1.1 gal. reserve tank)	5.2 gal. (19.7 L)
Reserve Fuel Capacity	1.1 gal. (4.2 L)
Oil Capacity	3.0 qts. (2.8 L)
Dry Weight	612.0 lbs. (277.8 kg)
Vehicle Weight In Running Order (int'l measure)	(295.1 kg)
Gross Vehicle Weight Rating	1085.0 lbs. (492.6 kg)

## ENGINE<sup>2</sup>

Engine	Twin Cam 88 (vibration isolation-mounted)
Valves	Pushrod-operated overhead valves; with hydraulic self-adjusting lifters; two valves per cylinder
Bore and Stroke	3.75 x 4.0 in. (95.25 x 101.6mm)
Displacement	88 cu. in. (1450 cc)
Compression Ratio	8.9:1
Fuel System	Carburetion (40 mm constant velocity with enricher and accelerator pump)
Air Cleaner/Filter	Oval with spun aluminum insert; high-efficiency, pleated paper filtration
Ignition	Single-fire, non-wasted, map-controlled spark ignition system; electronic breakerless with multiple advance curve matrix
Lubrication System	Dry sump, internally mounted, crank driven gerotor pressure and dual scavenge pump with spin on 10µ pressurized oil filter

## DRIVETRAIN

Primary Drive	Double-row chain; oil bath; mechanical tensioner; 25/36-tooth sprockets (1.44:1)
Final Drive	Gates aramid fiber reinforced Poly Chain belt; 32/70-tooth sprockets; 2.188:1
Clutch	Multi-plate with diaphragm spring in oil bath
Transmission	Five-speed, constant mesh
Gear Ratio:	
1st	10.110
2nd	6.958
3rd	4.953
4th	3.862
5th	3.150

## CHASSIS

Frame	Mild steel, rectangular section backbone with twin down-tubes
Swing Arm	Mild steel, rectangular section
Front Fork	Wide, 41.3 mm dia. forks with chrome fork triple clamp
Rear Shocks	Chrome coil-over with adjustable spring preload
Wheels	Wire laced front and rear
Brakes:	
Caliper type	Four-piston front and rear
Rotor type (diameter x width):	Patented, Uniform Expansion Rotors
Front	11.5 in. x .20 in. (292.1 mm x 5.08 mm)
Rear	11.5 in. x .23 in. (292.1 mm x 5.84 mm)
Suspension travel:	
Front wheel	5.6 in. (142.5 mm)
Rear wheel	4.3 in. (109 mm)

## PERFORMANCE<sup>3</sup>

Engine Torque	82.0 ft. lbs. @ 3500rpm (105.5 NM @ 3000 rpm)
Mileage (per E.P.A. test regulations):	
City	42 mpg (17.9 Km/L)
Highway	50 mpg (21.3 Km/L)
Braking at 60 mph (96.6 kph):	
Maximum load	165 ft. (49.5 m)
Lean Angle (per SAE J1168):	
Right	31 degrees
Left	32 degrees

## ELECTRIC

Battery	Sealed 12-volt, 19 amp-hour, 270cca (per Battery Council International rating)
Charging	32-amp permanent magnet alternator (360 watts @ 3,000 rpm, 416 watts peak) with solid -state regulator
Starting	1.2 kw electric with Bendix-type engagement
Lights: (As per country regulation)	
Headlamp	Quartz halogen 55-watt low beam, 60-watt high beam
Tail/stop lights	8w/28w
Turn signal lights	28w, self-canceling
Running lights	Integrated in front turn signals (except where prohibited by law)
Indicator lamps	High beam, neutral, oil pressure, engine diagnostic light, turn signals and security system (optional)

## STYLING/CONVENIENCE

Engine Trim	Black powdercoat with chrome covers
Exhaust System	Staggered chrome shorty duals with low interconnect
Oil Tank	Under-transmission
Front Fender	Custom with painted brace
Rear Fender	Custom sculpted Bobtail with chrome supports
Handlebars	Mini Ape-hanger with chrome riser
Windshield	none
Footpegs	Rubber-isolated operator and rubber-covered passenger
Forward foot position	Forward mounted brake and shift lever controls
Seat	Custom, stepped chopper seat with tucked pillow-look
Passenger Backrest	Chrome sideplates and sissy bar with H-D Eagle emblem and padded backrest
Saddlebags	none
Instruments	Large, tank-mounted electronic speedometer with odometer and resettable tripmeter in chrome tank console; fuel gauge
Fork Lock	Barrel-key on steering head, key common with ignition

## COLORS<sup>4</sup>

Vivid Black, Diamond Ice Pearl, Luxury Rich Red Pearl, Concord Purple Pearl  
 Chrome Yellow Pearl, Bronze Pearl, Two-Tone Luxury Rich Red/Black  
 Two-Tone Vivid Black/Chrome Yellow, New Two-Tone Luxury Blue/Diamond Ice  
 New Two-Tone Real Teal/Birch White

## WARRANTY

Warranty	12 months (unlimited mileage)
Service Interval	First 1,000 miles (1,600 Km); every 5,000 miles (8,000 Km) thereafter. <small>- Inspections of certain systems and components are required at 2,500 mile (4,000 Km) intervals -</small>

<sup>1</sup>Specifications for non-U.S. markets appear in parenthesis ( ). Harley-Davidson reserves the right to discontinue models or change specifications at any time without incurring any obligations. Vehicle specifications may vary from country to country depending on local laws, and some models are not available in certain countries.

<sup>2</sup>Additional Twin Cam 88 specs available. Select the powertrain button on menu.

<sup>3</sup>Based on tests conducted under lab conditions per U.S. E.P.A. test procedures. Mileage will vary depending on personal riding habits, weather conditions, trip length and vehicle condition.

<sup>4</sup>Availability may vary from dealer to dealer, and is subject to change without notice.